

SDSL-EL0190



Light Output Ratio:	100.0%
Luminaire Power:	198 W

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators:
Test Date: 2013-05-02

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%
Test Distance: 7.860m [K=1.0000]


MODEL :	SDSL-EL190
NORMALPOWER(W) :	198W
RATED VOLTAGE(V)	230v
NORMALFLUX(lm) :	18046LM
LAMPS INSIDE	1PC
TESTVOLTAGE:	230.01V
IMAX(cd) :	6824
BEAMANGLE:	106.5DEG
EFFENCY:	92.17lm/W

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:
Test Date:2013-05-02

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%
Test Distance:7.860m [K=1.0000]

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.01V I:0.9100A P:198W PF:0.9790 Lamp Flux:18046x1 lm		
NAME: LED Street Light	TYPE:Outdoots	WEIGHT:8.5
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:


INTENSITY DISTRIBUTION DIAGRAM
IN C PLANS

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators:
Test Date: 2013-05-02

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%
Test Distance: 7.860m [K=1.0000]

ISOCANDELA DIAGRAM


Test:U:230.01V I:0.9100A P:198W PF:0.9790 Lamp Flux:18046x1 lm		
NAME: LED Street Light	TYPE:Outdoots	WEIGHT:8.5
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:
Test Date:2013-05-02

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%
Test Distance:7.860m [K=1.0000]

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators:
Test Date: 2013-05-02

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%
Test Distance: 7.860m [K=1.0000]

AAI Figure

