

SDSL-EL0120



Light Output Ratio:	100.0%
Luminaire Power:	128 W

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2013-05-07

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%
Test Distance: 7.860m [K=1.0000]


MODEL :	SDSL-EL120
NORMALPOWER(W) :	128W
RATED VOLTAGE(V)	230v
NORMALFLUX(lm) :	11590.6LM
LAMPS INSIDE	1PC
TESTVOLTAGE:	230.01V
IMAX(cd) :	4318
BEAMANGLE:	127DEG
EFFENCY:	91.77lm/W

H(β) Range: 0-90360DEG
H(β) Interval: 0.0DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2013-05-03

V(β) Range: 0-180DEG
V(β) Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%
Test Distance: 7.860m [K=1.0000]

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.01V I:0.5850A P:128W PF:0.9810 Lamp Flux:11590.6x1 lm		
NAME: LED Street Light	TYPE:	WEIGHT:5
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:Mei Yuanping
Test Date:2013-05-07

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%
Test Distance:7.860m [K=1.0000]

ISOCANDELA DIAGRAM


Test:U:230.01V I:0.5850A P:128W PF:0.9810 Lamp Flux:11590.6x1 lm		
NAME: LED Street Light	TYPE:	WEIGHT:5
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2013-05-07

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%
Test Distance: 7.860m [K=1.0000]


Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2013-05-07

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%
Test Distance: 7.860m [K=1.0000]

AAI Figure



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2013-05-07

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%
Test Distance: 7.860m [K=1.0000]