
SDIP65-1200-T

Light Output Ratio:	100.0%
Luminaire Power:	40.5W

C Range: 0 - 180DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2014-2-20

γ Range: 0 - 90DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%


LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: LED Waterproof Tube Fixture	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:

MODEL:	SDIP65-1200-T
NORMALPOWER(W):	40.5W
RATED VOLTAGE(V)	230v
NORMALFLUX(lm):	4050.1LM
LAMPS INSIDE	1PC
TESTVOLTAGE:	230V
IMAX(cd):	1405
BEAMANGLE:	108DEG
EFFENCY:	104.12lm/W

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: LED Waterproof Tube Fixture	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:



C Range: 0 - 180DEG

Test Speed: MEDIUM

Temperature: 25DEG

Operators: Mei Yuanping

Test Date: 2014-2-20


 γ Range: 0 - 90DEG

Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279

Humidity: 90.0%

LDC(Linear)

NAME: LED Waterproof Tube Fixture	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




C Range: 0 - 180DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2014-2-20

γ Range: 0 - 90DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%

Lux distance Curve

NAME: LED Waterproof Tube Fixture	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 180DEG
 Test Speed: MEDIUM
 Temperature: 25DEG
 Operators: Mei Yuanping
 Test Date: 2014-2-20

γ Range: 0 - 90DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
 Humidity: 90.0%

Luminance Diagram

NAME: LED Waterproof Tube Fixture	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:



C Range: 0 - 180DEG
 Test Speed: MEDIUM
 Temperature:25DEG
 Operators:Mei Yuanping
 Test Date:2014-2-20

γ Range: 0 - 90DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
 Humidity:90.0%