

















LED Recessed canopy luminaire designed specifically industrial & exterior roofing canopies such as fuel stations, industrial food grade applications amongst others, finished in a rugged RAL White powder coated aluminium with tempered, stabilised, impact resistant PMMA lens, hence suitable for extreme climates & environments. With industrial applications in mind, the conopy light mount at heights up to 12m with up to 16,500lm makes this a unique direct replacement for 400W SON fittings, hence energy-efficiency, low luminous decay and maintenance were key factors in luminaire design. Long life means annual re-lamp, expensive lift equipment and inconvenience is negligible, as well as a much sought after energy savings of 75%. Further enhancments include high efficiency Meanwell™ driver the the heart of the luminaire, whilst further

## Product information

Durable with rated life span of +50,000 hours / No UV or IR emissions / Instant on & Flicker free / CE & RoHS international standards / Environmentally friendly & part recyclable: no mercury or other hazardous materials used / RAL White powder coated aluminium heat sink & PMMA optics / Meanwell™ Driver

Code	Nominal Size	Lumen Output	Power Consumption	Equivalent
SDCAN-060	350mm x 262mm x 72mm	6,600lm	60W	150W SON / 70W MHL
SDCAN-100	350mm x 343mm x 72mm	11,000lm	100W	250W SON / 150 MHL
SDCAN-150	350mm x426mm x 72mm	16,500lm	150W	400W SON / 250W MHL

Available in the following lumen finishes:

options of dimmable: DALI (-DL) / 1-10V (-AD).

Pure White

Other colours are available on request




LED Type: Epistar SMD3030 LED


Operating Temperature: -20°C to 50°C


Power Factor ≥ 0.95

Mounting Height: 5 - 12m


Colour Temperature: PW 5000K













## **LED Recessed Canopy**

60W / 100W / 150W

Pure White

F (+44)2920 099 091