
SDDL-012-4FR



Light Output Ratio:	100.0%
Luminaire Power:	12.154 W

C Range: 0 - 180DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2013-12-4

γ Range: 0 - 90DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: LED Ceiling Lamp	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:


MODEL:	SDDL-012-4FR
NORMALPOWER(W):	12.154W
RATED VOLTAGE(V)	230v
NORMALFLUX(lm):	686.77LM
LAMPS INSIDE	1PC
TESTVOLTAGE:	230V
IMAX(cd):	290.67
BEAMANGLE:	97.13DEG
EFFENCY:	56.51lm/W

C Range: 0 - 180DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:Mei Yuanping
Test Date:2013-12-4

γ Range: 0 - 90DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: LED Ceiling Lamp	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




C Range: 0 - 180DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2013-12-4

γ Range: 0 - 90DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%

LDC(Linear)

NAME: LED Ceiling Lamp	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




C Range: 0 - 180DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2013-12-4

γ Range: 0 - 90DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%

Lux distance Curve

NAME: LED Ceiling Lamp	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




Beam angle of C45plane97.13

C Range: 0 - 180DEG
 Test Speed: MEDIUM
 Temperature: 25DEG
 Operators: Mei Yuanping
 Test Date: 2013-12-4

Y Range: 0 - 90DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
 Humidity: 90.0%

Luminance Diagram

NAME: LED Ceiling Lamp	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:



C Range: 0 - 180DEG
 Test Speed: MEDIUM
 Temperature: 25DEG
 Operators: Mei Yuanping
 Test Date: 2013-12-4

γ Range: 0 - 90DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
 Humidity: 90.0%