

---

SDPL-0612

---

Light Output Ratio:	100.0%
Luminaire Power:	69.23 W

---

C Range: 0 - 180DEG  
Test Speed: MEDIUM  
Temperature: 25DEG  
Operators: Mei Yuanping  
Test Date: 2013-12-4

$\gamma$  Range: 0 - 90DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.279  
Humidity: 90.0%

## LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: LED Panel Light	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:


MODEL:	SDPL-0612
NORMALPOWER(W):	69.23W
RATED VOLTAGE(V)	230v
NORMALFLUX(lm):	5281.55LM
LAMPS INSIDE	1PC
TESTVOLTAGE:	230.08V
IMAX(cd):	1828.202
BEAMANGLE:	112.99DEG
EFFENCY:	76.3lm/W

C Range: 0 - 180DEG  
Test Speed: MEDIUM  
Temperature:25DEG  
Operators:Mei Yuanping  
Test Date:2013-12-4

$\gamma$  Range: 0 - 90DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.279  
Humidity:90.0%

## LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: LED Panel Light	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




C Range: 0 - 180DEG  
Test Speed: MEDIUM  
Temperature: 25DEG  
Operators: Mei Yuanping  
Test Date: 2013-12-4

$\gamma$  Range: 0 - 90DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.279  
Humidity: 90.0%

## LDC(Linear)

NAME: LED Panel Light	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




C Range: 0 - 180DEG  
Test Speed: MEDIUM  
Temperature: 25DEG  
Operators: Mei Yuanping  
Test Date: 2013-12-4

γ Range: 0 - 90DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.279  
Humidity: 90.0%

## Lux distance Curve

NAME: LED Panel Light	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




Beam angle of C135plane112.99

C Range: 0 - 180DEG  
 Test Speed: MEDIUM  
 Temperature: 25DEG  
 Operators: Mei Yuanping  
 Test Date: 2013-12-4

γ Range: 0 - 90DEG  
 Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.279  
 Humidity: 90.0%

## Luminance Diagram

NAME: LED Panel Light	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:



C Range: 0 - 180DEG  
Test Speed: MEDIUM  
Temperature: 25DEG  
Operators: Mei Yuanping  
Test Date: 2013-12-4

γ Range: 0 - 90DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.279  
Humidity: 90.0%