


SDSL-EL150



Light Output Ratio:	100.0%
Luminaire Power:	158 W

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2013-05-03

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%
Test Distance: 7.860m [K=1.0000]


MODEL:	SDSL-EL150
NORMALPOWER(W):	158W
RATED VOLTAGE(V)	230v
NORMALFLUX(lm):	14388.8LM
LAMPS INSIDE	1PC
TESTVOLTAGE:	230.01V
IMAX(cd):	5444
BEAMANGLE:	105.9DEG
EFFENCY:	92.18lm/W

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:Mei Yuanping
Test Date:2013-05-03

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%
Test Distance:7.860m [K=1.0000]

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.01V I:0.7280A P:158W PF:0.9760 Lamp Flux:14388.8x1 lm		
NAME: LED Street Light	TYPE:	WEIGHT:5.5
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:


INTENSITY DISTRIBUTION DIAGRAM
IN C PLANS

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: MEDIUM
 Temperature: 25DEG
 Operators: Mei Yuanping
 Test Date: 2013-05-03

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
 Humidity: 90.0%
 Test Distance: 7.860m [K=1.0000]

ISOCANDELA DIAGRAM


Test:U:230.01V I:0.7280A P:158W PF:0.9760 Lamp Flux:14388.8x1 lm		
NAME: LED Street Light	TYPE:	WEIGHT:5.5
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:Mei Yuanping
Test Date:2013-05-03

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%
Test Distance:7.860m [K=1.0000]


Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: MEDIUM
Temperature: 25DEG
Operators: Mei Yuanping
Test Date: 2013-05-03

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity: 90.0%
Test Distance: 7.860m [K=1.0000]

AAI Figure



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: MEDIUM
 Temperature: 25DEG
 Operators: Mei Yuanping
 Test Date: 2013-05-03

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
 Humidity: 90.0%
 Test Distance: 7.860m [K=1.0000]