

SDSL-EL060



Light Output Ratio:	100.0%
Luminaire Power:	62.9 W
90% Beam Spread	28.9V x 121.5H
50% Beam Lumens	782.2 lumens per klm.

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:Mei Yuanping
Test Date:2013-05-03

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%
Test Distance:7.860m [K=1.0000]


MODEL :	SDSL-EL060
NORMALPOWER(W) :	62.9W
RATED VOLTAGE(V)	230v
NORMALFLUX(lm) :	5657.88LM
LAMPS INSIDE	1PC
TESTVOLTAGE:	230.01V
IMAX(cd) :	2097
BEAMANGLE:	113DEG
EFFENCY:	89.95lm/W

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:Mei Yuanping
Test Date:2013-05-03

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%
Test Distance:7.860m [K=1.0000]

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.01V I:0.2880A P:62.90W PF:0.9910 Lamp Flux:5657.88x1 lm		
NAME: LED Street Light	TYPE:	WEIGHT:3
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:Mei Yuanping
Test Date:2013-05-03

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%
Test Distance:7.860m [K=1.0000]

Luminance Diagram

Test:U:230.01V I:0.2880A P:62.90W PF:0.9910 Lamp Flux:5657.88x1 lm		
NAME: LED Street Light	TYPE:	WEIGHT:3
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:Mei Yuanping
Test Date:2013-05-03

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%
Test Distance:7.860m [K=1.0000]

AAI Figure


Test:U:219.9V I:0.2880A P:62.90W PF:0.9910 Lamp Flux:5657.88x1 lm		
NAME: LED Street Light	TYPE:	WEIGHT:3
SPEC.:	DIM.:	SERIAL No.:
MFR.: Sedna LED Ltd	SUR.:	PROTECTION ANGLE:



H(β) Range:-90 - 90DEG
 H(β) Interval: 0.5DEG
 Test Speed: MEDIUM
 Temperature: 25DEG
 Operators: Mei Yuanping
 Test Date: 2013-05-03

V(B) Range:-180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.279
 Humidity: 90.0%
 Test Distance: 7.860m [K=1.0000]

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: MEDIUM
Temperature:25DEG
Operators:Mei Yuanping
Test Date:2013-05-03

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.279
Humidity:90.0%
Test Distance:7.860m [K=1.0000]